

Izjava o svojstvima Nr.: 02-BAB-ETA-09/0256

- 1. Jedinstvena identifikacijska oznaka proizvoda:**
ETA-09/0256 Baunit open
- 2. Vrsta, partija ili serijski broj ili neki drugi element koji omogućuje identifikaciju građevnog proizvoda kako je zahtevano u skladu sa člankom 11 stavak 4:**
Baunit open
- 3. Namjeravan uporab građevnog proizvoda, u skladu sa primjenjivom usklađenom tehničkom specifikacijom, kako ju je predvidio proizvođač:**
Povezani sustav za vanjsku toplinsku izolaciju
- 4. Naziv, registrirani trgovački naziv ili registrirani trgovački žig i kontaktna adresa proizvođača kako se zahtjeva u skladu sa člankom 11., stavak 5.:**
Baunit Beteiligungen GmbH
Wopfing 156
A-2754 Waldegg
- 5. Naziv i kontaktna adresa ovlaštenog predstavnika čije ovlaštenje obuhvaća zadatke određene u članku 12, stavak 2:**
/ (Hr. Direktor Alfred Gsandtner)
- 6. Sustav ili sustavi i provjere stalnosti svojstava građevnog proizvoda prema prilogu V:**
Sustav 1 (reakcija na požar)
Sustav 2+ (ETAG 004, izuzev reakcije na požar)
- 7. Izjava o svojstvima za ovaj ETICS sustav izdaje se na temelju europskog tehničkog dopuštenja izdanog od:**
 - a. TSUS, Studená 3, 821 04 Bratislava, Slowakei
temeljem: ETAG 004
Izdaje se: ETA-09/0256
 - b. WIEN-ZERT, Rinnböckstraße 15, 1110 Wien, Österreich
temeljem: ETA-09/0256, poglavlje 3 proveo je ispitivanje i ocjenjivanje stalnosti svojstava prema sustavu 1 **te izdao Potvrdu o ispitivanju** 1139-CPD-0757/09
 - c. WIEN-ZERT, Rinnböckstraße 15, 1110 Wien, Österreich
temeljem: ETA-09/0256, poglavlje 3 proveo je ispitivanje i ocjenjivanje stalnosti svojstava prema sustavu 2+ **te izdao Potvrdu o ispitivanju** 1139-CPD-0756/09

8. Objavljena svojstva

Svojstva	Vrijednost	Tehnička specifikacija
Reakcija na požar	B – s1, d0	ETAG 004:2013
Vodoupojnost nakon 24 h	< 0,5 kg/m ²	ETAG 004:2013
Vlažnosno toplinski utjecaji	otporno	ETAG 004:2013
Otpornost na smrzavanje-odmrzavanje	NPD	ETAG 004:2013
Otpornost na udar	Klasa II	ETAG 004:2013
Otpornost na udar (Baumit Creativ-Top; Baumit NanoporFine)	Klasa III	ETAG 004:2013
Otpornost na udar (Baumit Fine-Top)	NPD	ETAG 004:2013
Paropropusnost	≤ 2 m	ETAG 004:2013
Oslobađanje štetnih tvari	NPD	ETAG 004:2013
Vlačna čvrstoća:		ETAG 004:2013
armaturni sloj – izolacija	≥ 0,08 MPa ili lom u izolacijskom materijalu	ETAG 004:2013
ljepilo – izolacija	≥ 0,08 MPa izlazna vrijednost ili lom u izolaciji ≥ 0,03 MPa 48 h potapanje ili lom u izolaciji ≥ 0,08 MPa 48 h potapanje + 7 dana 23 °C / 50 % rel.vlage ili lom u izolaciji	ETAG 004:2013
ljepilo – podloga	≥ 0,25 MPa izlazna vrijednost ≥ 0,08 MPa 48 h potapanje + 2 h 23 °C / 50 % rel.vlage ≥ 0,25 MPa 48 h potapanje + 7 dana 23 °C / 50 % rel.vlage	ETAG 004:2013
Posmična čvrstoća (proba posmi-kom)	NPD	ETAG 004:2013
Otpornost na opterećenje vjetrom	Ne u spoju ploča: min. 400 N U spoju ploča: min. 400 N Vlaga: NPD	ETAG 004:2013
Koeficijent toplinskog otpora	R ≤ 1 m ² K/W	ETAG 004:2013
Vlačna čvrstoća prionljivosti nakon starenja	≥ 0,08 MPa ili u lom u izolaciji	ETAG 004:2013

9. Svojstva sklopa za toplinsku izolaciju prema točki 1 i 2 odgovaraju objavljenim karakteristikama u točki 8. Ova Izjava o svojstvima objavljuje se isključivo pod odgovornošću proizvođača čiji su podaci iskazani u točki 4.

Ime i potpis proizvođača:

.....Dorijan Rajković direktor
(Ime i funkcija)

.....Zagreb 20.4.2018.....
(mjesto i datum izdavanja)


BAUMIT d.o.o., Sirač

.....
(Potpis)



Technický a skúšobný ústav stavebný, n. o.
Building Testing and Research Institute
Studená 3
821 04 Bratislava
Slovak Republic
Phone: +421 2 49228101
E-mail: sternova@tsus.sk
Website: www.tsus.sk



European Technical Assessment

ETA 09/0256
of 08/09/2014

General Part

Technical Assessment Body issuing the ETA and designated according to Article 29 of the Regulation (EU) No 305/2011: **Technický a skúšobný ústav stavebný, n. o.**

Trade name of the construction product

Baunit open

Product family to which the construction product belongs

Product area code: 4
External Thermal Insulation Composite Systems with rendering on expanded polystyrene (EPS) for the use as external insulation to walls of buildings

Manufacturer

Baunit Beteiligungen GmbH
Wopfing 156
A-2754 Waldegg
Austria
<http://www.baunit.at>

Manufacturing plant

Baunit Beteiligungen GmbH
Wopfing 156
A-2754 Waldegg
Austria

This European Technical Assessment contains

31 pages including 4 annexes which form an integral part of this assessment.

This European Technical Assessment is issued in accordance with regulation (EU) No 305/2011, on the basis of

ETAG 004, edition June 2013, used as European Assessment Document (EAD).

This version replaces

ETA-09/0256 with validity from 10.06.2013 to 09.06.2018